

Micro Replus Gateway (MRG)

Features:

- Aesthetically pleasing with a durable design and airtight sealing. Easy-to-use energy saving touch screen LCD display provides real time system performance monitoring
- Embedded with state of the art and latest software technology. Power Line Carrier (PLC) mode provides inverter communication. Smart internal memory card integration (available in 256 MB or 1 GB) stores performance data for up to 20 years. Local monitoring via Ethernet connection allows accurate web page monitoring of the inverter's operating status
- Supports various external hardware such as a USB keyboard
- Remote intelligent monitoring allows user to login and monitor system performance anytime from anywhere
- Small size, light weight, and use minimal power



Europe

Add: Renesola Deutschland GmbH, Lyoner Strasse 15,
60529 Frankfurt/M, Germany
T: +49 69 663 786 9-0

Australia

Add: 18 Corporate Blvd. Bayswater,
VIC 3153, Australia
T: +61 481 251 275

Web: www.renesola.com
E: inverter@renesola.com

Technical specifications:

Operating voltage	69 V to 230 V
Operating frequency	50 / 60 Hz
Number of monitored inverters	1 to 255
Protection	IP20
Ambient temperature	-20°C to +55°C
communication	PLC / 10 M / 100 M Ethernet
Power consumption	< 5 W
Dimensions (D x W x H)	37 x 148 x 113 mm
Weight	342 g / 0.75 lbs
Standard warranty period	1 year